
Calpeda NGX Series



- Horizontal multi stage closed coupled self priming shallow well pump with built in ejector
- A high quality pump for domestic water supply
- Ideal for poor suction situations with a suction depth of up to 8 m
- Suitable for water supply and domestic use
- Stainless steel
- Self priming



FLOW (I/min)




PERFORMANCE GUIDE						
Code	Max Head (m)	Max Flow (I/min)	Max Pressure (psi)	Max Suction Depth (m)	Inlet (mm)	Outlet (mm)
PUCALNGXM2/80M	46	55	65	7	25	25
PUCALNGX3/100M	50	60	70	7	25	25
PUCALNGX4/110M	42	75	60	7	25	25
PUCALNGXM4/16M	57.5	75	82	7	32	25


ELECTRICAL DATA									
Code	Current Type	kW	Нр	Amps	RPM/min	Capacitor (µF)	Insulation Class	Voltage (V)	Frequency (Hz)
PUCALNGXM2/80M	Single	0.55	0.8	3.8	2800	16	F	230	50
PUCALNGX3/100M	Single	0.65	0.9	4.5	2800	16	F	230	50
PUCALNGX4/110M	Single	0.75	1.0	5.4	2800	20	F	230	50
PUCALNGXM4/16M	Single	1.1	1.5	7	2800	30	F	230	50



Calpeda NGX Series

- **calpeda**
- Horizontal multi stage closed coupled self priming shallow well pump with built in ejector
- A high quality pump for domestic water supply
- Ideal for poor suction situations with a suction depth of up to 8m
- Suitable for water supply and domestic use
- Stainless steel
- Self priming





DIMENSIONS + WEIGHTS						
Code	fM (mm)	L (mm)	H (mm)	h1 (mm)	Weight (kg)	
PUCALNGXM2/80M	362	161	176	116	7.1	
PUCALNGX3/100M	391	161	192	116	9.2	
PUCALNGX4/110M	391	161	192	116	14.8	
PUCALNGXM4/16M	462	213.5	225	152	16.7	

SERVICE PARTS + KITS					
Code	Component	Size (mm)	Pump		
PUCALNGX2/80S/KIT	Service kit	-	NGX2/80		

