

SCR drive fractional permanent magnet motor, TENV and TEFC, C-Face with base 1/4 thru 5 Hp



Features:

- NEMA C-Face with removable base
- Tachometer adaptable
- Class F insulation
- Double sealed bearings
- 20:1 constant torque speed range
- UL and CSA recognized

Applications:

- Conveyors
- Mixers
- Packaging machinery

Hp	Base Speed	NEMA Frame	Voltage	Full Load	Enclosure	Catalog Number	List Price	Disc. Sym.	Ap'x. Shpg. Wgt.	XPY Tach MTG Kit	Notes (a)
			D.C. Arm.	Amperage Arm.							
1/4	1750	56C	90	2.5	TENV	CDP3310	1,179	PMS	24	TK3300	20,60
			180	1.25	TENV	CDP3306	1,179	PMS	23	TK3300	20,60
1/3	1750	56C	90	3.2	TENV	CDP3320	1,391	PMS	27	TK3300	20,60
			180	1.6	TENV	CDP3316	1,243	PMS	27	TK3300	20,60
1/2	1750	56C	90	4.8	TENV	CDP3330	1,391	PMS	32	TK3300	20,60
			180	2.5	TENV	CDP3326	1,391	PMS	31	TK3300	20,60
	2500	56C	90	5	TENV	CDP3335	1,243	PMS	26	TK3300	20,60
			90	7.6	TEFC	CDP3440	1,689	PMS	38	TK3400	20
3/4	1750	56C	180	3.7	TEFC	CDP3436	1,689	PMS	38	TK3400	20
			2500	56C	90	7.5	TEFC	CDP3443	1,495	PMS	36
	1750	56C	90	10	TEFC	CDP3445	2,055	PMS	44	TK3400	20
			180	5	TEFC	CDP3455	2,055	PMS	44	TK3400	20
1	2500	56C	90	9.7	TEFC	CDP3450	1,689	PMS	38	TK3400	20
			180	4.85	TEFC	CDP3460	1,689	PMS	38	TK3400	20
1 1/2	1750	145TC	180	7.7	TEFC	CDP3575	3,784	PMS	65	TK3500	20
			2500	145TC	180	7	TEFC	CDP3580	3,293	PMS	53
2	1750	145TC	180	9.6	TEFC	CDP3585	4,515	PMS	74	TK3500	20
			2500	145TC	180	10	TEFC	CDP3590	3,784	PMS	66
3	1750	182TC	180	14	TEFC	CDP3603	5,561	PMS	112	TK3600PM	20
			182C	180	14	TEFC	CDP3604	5,530	PMS	112	TK3600PM
5	1750	1810ATC	180	21.6	TEFC	CDP3605	9,437	PMS	161	TK3600PM	20

Note: See Tach Generators and Mounting Kits.

(a) See notes on inside back flap.